FENIX NTA® SPECIFICATION GUIDELINES



March 2022

Points to remember when specifying FENIX NTA® (Nano Tech Alloy):

- **1.** Specify product distributor: Architectural Products & Technologies (APT)
 - (Please note that FENIX NTA[®] is made only by Arpa Industriale and is only distributed in NZ by APT)
- 2. Specify nominal thickness:
 - FENIX NTA[®] is available in 0.7mm as standard or 1.2mm Colour Core for horizontal or vertical interior joinery applications.

3. Specify backing option for benchtop or cabinetry:

- For benchtops thinner than 20mm total thickness we recommend an Arpa backing laminate is specified, regardless of substrate.
- For shelving or cabinetry doors we recommend that you specify FENIX NTA[®] doublesided on a moisture-resistant substrate no thinner than 18mm.

4. Specify edging option:

- 0.7mm FENIX NTA[®] edging will give a black join line, exactly the same as a high pressure laminate would do; alternatively
- 1.2mm FENIX NTA[®] colour core edging

5. Specify exact FENIX NTA[®] colour(s) by name and if possible the code

Please visit our website at <u>www.fenix.co.nz</u> for NZ stock range colours.

6. Specify fabrication and installation:

 To ensure that the fabrication of your job meets the requirements for the FENIX NTA[®] warranty, specify that the work must be carried out by a qualified benchtop fabricator or joinery company, using best trade practices.

7. Please add our details to the finishing schedule and send us a copy so that we can ensure we have the stock for your project.

- Architectural Products & Technologies (APT)
- Phone: 0800 267 426
- sales@aptinnovation.co.nz

FENIX NTA® SPECIFICATION GUIDELINES

FENIX NTA[®] is a REAL METAL ALLOY and can be used anywhere you would consider utilising a High Pressure or Low Pressure laminate as a decorative surface in Commercial and Residential applications – for example:

- Kitchen, bathroom, laundry bench tops & cabinetry.
- Furniture tables, bedside tables, bookshelves, chairs.
- Shelving.
- Reception counters.
- Wall paneling.
- Toilet partitioning, doors.

Please note:

- FENIX NTA[®] is only for suitable for square edges to bench tops and tables etc.; it cannot be Post Formed.
- A Shallow Arc with minimum 150 mm radius is achievable.
- FENIX NTA[®] is NOT recommended for use as a splashback.
- FENIX **NTA**[®] is for interior use only.
- FENIX NTA[®] is directional. Grain direction is indicated by the arrows on the protective film.